



## **DSC-W310**

#### 12.1 MP | 4x OPTICAL ZOOM | 2.7" LCD1

The DSC-W310 is the digital camera for those looking a slim camera with a strong feature and value propositions. Capture amazingly detailed images from farther away with the DSC-W310's professional quality 4x Sony Lens. With advanced features including SteadyShot® image stabilization, iAUTO and Smile Shutter™ technology, the DSC-W310 makes taking the best shot a cinch.



# 28mm equivalent Sony lens with 4x optical zoom

With a Sony 4x optical zoom (28mm equivalent) wide-angle lens, you can take great shots from greater distances plus better group shots in tight spots.

#### Minimize blur in your shots

SteadyShot® image stabilization compensates for camera shake and helps prevent blur through use of digital processing technologies.

#### Enjoy automatic adjustment of key camera settings

Unlike traditional auto mode, Intelligent Auto (iAUTO) mode thinks for you, recognizing scenes, lighting conditions, faces, and adjusts settings resulting clear images, faces with natural skin tone and less blur. With iAUTO you will take the best shot in many situations from landscapes to fast action sporting events without having to manually change all of the cameras settings.

# Take better photos under 7 different shooting conditions—automatically

Intelligent Scene Recognition (iSCN) Mode detects specific shooting conditions for 7 common scenarios, including: Twilight, Twilight Portrait, Backlight, Backlight Portrait, Landscape, Macro, and Portrait. In just 1/30th of a second, the camera automatically optimizes its settings for the selected scene.

### Get those winning smiles every time

Smile Shutter™ technology snaps a photo of a smile the moment it happens. Simply press the Smile Shutter™ button and the camera does the rest. This function can also be used in conjunction with Intelligent Scene Recognition to detect smiles in challenging backlit environments, employing a flash and backlight compensation to capture smiles more clearly.

# Take more natural-looking shots of people

Face Detection technology detects up to eight individual faces in the frame, then adjusts the camera's focus, exposure, and flash to deliver crisp, properly lit images of family and friends.

### Access simplified camera operations

Even the most novice of digital camera users can take the best shot using Easy Shooting Mode. This feature uses the camera's Intelligent Scene Recognition capability to automatically adjust its settings based on different shooting scenarios. In this mode, the LCD screen only displays basic, easy-to-understand functions to simplify your experience.

#### Edit photos on the fly

Retouch and enhance your photos on the go with in-camera Trimming and Red-Eye Correction functions.

### Choose from 8 convenient scene modes

The DSC-W310 features 8 different scene modes: High Sensitivity, Twilight, Twilight Portrait, Soft Snap, Landscape, Beach, Snow and Gourmet. Once a mode has been selected, the camera optimizes its settings to help you get the best shot possible.

#### Additional features:

- VGA movie capabilities
- · High sensitivity ISO 3200
- Find your photos using the simple folder or calendar viewing modes
- Function Guide helps explain menus and settings
- Card slot for optional Memory Stick Duo™ and SD/SDHC media<sup>13</sup>
- Includes PMB (Picture Motion Browser)<sup>2</sup> and PMB Portable Software<sup>3</sup>

### **Specifications**

Seneral	
Camera Type	Entry Level Compact Point and Shoot
Image Device	1/2.3" (7.79mm) Super HAD™ CCD
Effective Pixels Resolution	12.1MP
Processor	Yes
Optics & Lens	
Lens Type	Sony Lens
Lens Construction	6 elements in 5 groups
Aperture Range	iAUTO(F3.0/F4.3(W), 2 steps) / Program Auto(F3.0/F4.3(W), 2 steps)
Focal Length	5-20mm
35mm Equivalency	Still shots: 28-112mm / Movie 4:3: 28-112mm
Optical Zoom	4x
Digital Zoom	Smart Zoom / Precision Digital Zoom / Off
Total Zoom	Approximately 8x with Precision Digital Zoom
CD & Viewfinder	
LCD Type	2.7" Clear Photo™ LCD¹ (230K)
Viewfinder	-
Recording Media Slot	MS PRO Duo™ media / SD/SDHC media <sup>13</sup>
Media 3101	12M (4,000 x 3,000) / 8M (3,264 x 2,448) /
Still Images	5M (2,592 x 1,944) / VGA (640 x 480); 16:9
om mages	9M(4,000 x 2,248) / 2M(1,920 x1,080)
	VGA(640 x 480) (29.97fps, Progressive) /
Video	QVGA (320 x 240) (29.97fps, Progressive)
Microphone / Speaker	Mono / Mono
ocus	
Focus	9 points AF / Center Weighted AF
Focus Intelligent Auto Focus	-
	iAUTO(W:Approx. 5cm (1.96") to Infinity, T:Approx.
Intelligent Auto Focus Macro Mode	-
Intelligent Auto Focus	iAUTO(W:Approx. 5cm (1.96") to Infinity, T:Approx.
Intelligent Auto Focus  Macro Mode  xposure	iAUTO(W:Approx. 5cm (1.96°) to Infinity, T:Approx. 50cm (19.7°) to Infinity)
Intelligent Auto Focus Macro Mode  Xposure  Exposure Metering Exposure Compensation ISO	iAUTO(W:Approx. 5cm (1.96°) to Infinity, T:Approx. 50cm (19.7°) to Infinity)  Multi Pattern / Center Weighted / Spot
Intelligent Auto Focus Macro Mode  xposure Exposure Metering Exposure Compensation ISO Backlight Correction HDR	iAUTO(W:Approx. 5cm (1.96°) to Infinity, T:Approx. 50cm (19.7°) to Infinity)  Multi Pattern / Center Weighted / Spot Plus / Minus 2.0EV, 1 / 3EV step
Intelligent Auto Focus Macro Mode  Xposure  Exposure Metering Exposure Compensation ISO	iAUTO(W:Approx. 5cm (1.96°) to Infinity, T:Approx. 50cm (19.7°) to Infinity)  Multi Pattern / Center Weighted / Spot Plus / Minus 2.0EV, 1 / 3EV step Auto / 100 / 200 / 400 / 800 / 1600 / 3200
Intelligent Auto Focus Macro Mode  xposure Exposure Metering Exposure Compensation ISO Backlight Correction HDR	- iAUTO(W:Approx. 5cm (1.96°) to Infinity, T:Approx. 50cm (19.7°) to Infinity)  Multi Pattern / Center Weighted / Spot Plus / Minus 2.0EV, 1 / 3EV step Auto / 100 / 200 / 400 / 800 / 1600 / 3200 Auto / Daylight / Cloudy / Fluorescent 1 (White
Intelligent Auto Focus Macro Mode  xposure Exposure Metering Exposure Compensation ISO Backlight Correction HDR	iAUTO(W:Approx. 5cm (1.96*) to Infinity, T:Approx. 50cm (19.7*) to Infinity)  Multi Pattern / Center Weighted / Spot Plus / Minus 2.0EV, 1 / 3EV step Auto / 100 / 200 / 400 / 800 / 1600 / 3200  - Auto / Daylight / Cloudy / Fluorescent 1 (White Fluorescent Lighting) / Fluorescent 2 (Natural
Intelligent Auto Focus Macro Mode  xposure Exposure Metering Exposure Compensation ISO Backlight Correction HDR Dynamic Range Optimizer	iAUTO(W:Approx. 5cm (1.96*) to Infinity, T:Approx. 50cm (19.7*) to Infinity)  Multi Pattern / Center Weighted / Spot Plus / Minus 2.0EV. 1 / 3EV step Auto / 100 / 200 / 400 / 800 / 1600 / 3200  Auto / Daylight / Cloudy / Fluorescent 1 (White Fluorescent Lighting) / Fluorescent 2 (Natural White Fluorescent Lighting) / Fluorescent 3 (Day
Intelligent Auto Focus Macro Mode  xposure Exposure Metering Exposure Compensation ISO Backlight Correction HDR Dynamic Range Optimizer  White Balance	iAUTO(W:Approx. 5cm (1.96*) to Infinity, T:Approx. 50cm (19.7*) to Infinity)  Multi Pattern / Center Weighted / Spot Plus / Minus 2.0EV. 1 / 3EV step Auto / 100 / 200 / 400 / 800 / 1600 / 3200  Auto / Daylight / Cloudy / Fluorescent 1 (White Fluorescent Lighting) / Fluorescent 2 (Natural White Fluorescent Lighting) / Fluorescent 3 (Day
Intelligent Auto Focus Macro Mode  xposure Exposure Metering Exposure Compensation ISO Backlight Correction HDR Dynamic Range Optimizer	iAUTO(W:Approx. 5cm (1.96°) to Infinity, T:Approx. 50cm (19.7°) to Infinity)  Multi Pattern / Center Weighted / Spot Plus / Minus 2.0EV, 1 / 3EV step Auto / 100 / 200 / 400 / 800 / 1600 / 3200  - Auto / Daylight / Cloudy / Fluorescent 1 (White Fluorescent Lighting) / Fluorescent 2 (Natural White Fluorescent Lighting) / Fluorescent 3 (Day White Fluorescent Lighting) / Incandescent / Flash
Intelligent Auto Focus Macro Mode  xposure Exposure Metering Exposure Compensation ISO Backlight Correction HDR Dynamic Range Optimizer  White Balance  hutter Shutter Speed	iAUTO(W:Approx. 5cm (1.96°) to Infinity, T:Approx. 50cm (19.7°) to Infinity)  Multi Pattern / Center Weighted / Spot Plus / Minus 2.0EV, 1 / 3EV step Auto / 100 / 200 / 400 / 800 / 1600 / 3200  - Auto / Daylight / Cloudy / Fluorescent 1 (White Fluorescent Lighting) / Fluorescent 2 (Natural White Fluorescent Lighting) / Fluorescent 3 (Day White Fluorescent Lighting) / Incandescent / Flash
Intelligent Auto Focus Macro Mode  xposure Exposure Metering Exposure Compensation ISO Backlight Correction HDR Dynamic Range Optimizer  White Balance  hutter Shutter Speed Burst Mode	iAUTO(W:Approx. 5cm (1.96*) to Infinity, T:Approx. 50cm (19.7*) to Infinity)  Multi Pattern / Center Weighted / Spot Plus / Minus 2.0EV, 1 / 3EV step Auto / 100 / 200 / 400 / 800 / 1600 / 3200  - Auto / Daylight / Cloudy / Fluorescent 1 (White Fluorescent Lighting) / Fluorescent 2 (Natural White Fluorescent Lighting) / Fluorescent 3 (Day White Fluorescent Lighting) / Incandescent / Flash  iAUTO(1/4" - 1/2,000) / Program Auto(1" - 1/2,000)
Intelligent Auto Focus Macro Mode  Xposure Exposure Metering Exposure Compensation ISO Backlight Correction HDR Dynamic Range Optimizer  White Balance  hutter Shutter Speed Burst Mode  lash	iAUTO(W:Approx. 5cm (1.96*) to Infinity, T:Approx. 50cm (19.7*) to Infinity)  Multi Pattern / Center Weighted / Spot Plus / Minus 2.0EV, 1 / 3EV step Auto / 100 / 200 / 400 / 800 / 1600 / 3200  - Auto / Daylight / Cloudy / Fluorescent 1 (White Fluorescent Lighting) / Fluorescent 2 (Natural White Fluorescent Lighting) / Fluorescent 3 (Day White Fluorescent Lighting) / Incandescent /Flash  iAUTO(1/4* - 1/2,000) / Program Auto(1* - 1/2,000) Normal / Burst (Approx.0.85 fps at 12.1MP (Maximum 100 shots))
Intelligent Auto Focus Macro Mode  xposure Exposure Metering Exposure Compensation ISO Backlight Correction HDR Dynamic Range Optimizer  White Balance  hutter Shutter Speed Burst Mode	iAUTO(W:Approx. 5cm (1.96*) to Infinity, T:Approx. 50cm (19.7*) to Infinity)  Multi Pattern / Center Weighted / Spot Plus / Minus 2.0EV, 1 / 3EV step Auto / 100 / 200 / 400 / 800 / 1600 / 3200  Auto / Daylight / Cloudy / Fluorescent 1 (White Fluorescent Lighting) / Fluorescent 2 (Natural White Fluorescent Lighting) / Fluorescent 3 (Day White Fluorescent Lighting) / Incandescent /Flash  iAUTO(1/4" - 1/2,000) / Program Auto(1" - 1/2,000) Normal / Burst (Approx.0.85 fps at 12.1MP (Maximum 100 shots))
Intelligent Auto Focus Macro Mode  Xposure Exposure Metering Exposure Compensation ISO Backlight Correction HDR Dynamic Range Optimizer  White Balance  hutter Shutter Speed Burst Mode  lash	iAUTO(W:Approx. 5cm (1.96*) to Infinity, T:Approx. 50cm (19.7*) to Infinity)  Multi Pattern / Center Weighted / Spot Plus / Minus 2.0EV. 1 / 3EV step Auto / 100 / 200 / 400 / 800 / 1600 / 3200
Intelligent Auto Focus Macro Mode  xposure  Exposure Metering Exposure Compensation ISO Backlight Correction HDR Dynamic Range Optimizer  White Balance  hutter Shutter Speed Burst Mode  lash Flash Type	iAUTO(W:Approx. 5cm (1.96*) to Infinity, T:Approx. 50cm (19.7*) to Infinity)  Multi Pattern / Center Weighted / Spot Plus / Minus 2.0EV, 1 / 3EV step Auto / 100 / 200 / 400 / 800 / 1600 / 3200  - Auto / Daylight / Cloudy / Fluorescent 1 (White Fluorescent Lighting) / Fluorescent 2 (Natural White Fluorescent Lighting) / Fluorescent 3 (Day White Fluorescent Lighting) / Incandescent /Flash  iAUTO(1/4" - 1/2.000) / Program Auto(1" - 1/2,000) Normal / Burst (Approx.0.85 fps at 12.1MP (Maximum 100 shots))  Built-In ISO Auto: Approx.0.5 - Approx.3.0m (Approx.1.64'-Approx.9.84')(W) / Approx.0.5 -
Intelligent Auto Focus Macro Mode  Xposure Exposure Metering Exposure Compensation ISO Backlight Correction HDR Dynamic Range Optimizer  White Balance  hutter Shutter Speed Burst Mode  lash	iAUTO(W:Approx. 5cm (1.96*) to Infinity, T:Approx. 50cm (19.7*) to Infinity)  Multi Pattern / Center Weighted / Spot Plus / Minus 2.0EV, 1 / 3EV step Auto / 100 / 200 / 400 / 800 / 1600 / 3200  - Auto / Daylight / Cloudy / Fluorescent 1 (White Fluorescent Lighting) / Fluorescent 2 (Natural White Fluorescent Lighting) / Fluorescent 3 (Day White Fluorescent Lighting) / Incandescent /Flash  iAUTO(1/4* - 1/2.000) / Program Auto(1* - 1/2.000) Normal / Burst (Approx.0.85 fps at 12.1MP (Maximum 100 shots))  Built-In ISO Auto: Approx.0.5 - Approx.3.0m (Approx.1.64'-Approx.9.84')(W) / Approx.0.5 - Approx.1.5 m(Approx.1.64'-Approx.4.92')(T),
Intelligent Auto Focus Macro Mode  xposure  Exposure Metering Exposure Compensation ISO Backlight Correction HDR Dynamic Range Optimizer  White Balance  hutter Shutter Speed Burst Mode  lash Flash Type	iAUTO(W:Approx. 5cm (1.96°) to Infinity, T:Approx. 50cm (19.7°) to Infinity)  Multi Pattern / Center Weighted / Spot Plus / Minus 2.0EV, 1 / 3EV step Auto / 100 / 200 / 400 / 800 / 1600 / 3200  - Auto / Daylight / Cloudy / Fluorescent 1 (White Fluorescent Lighting) / Fluorescent 2 (Natural White Fluorescent Lighting) / Fluorescent 3 (Day White Fluorescent Lighting) / Incandescent /Flash iAUTO(1/4" - 1/2,000) / Program Auto(1" - 1/2,000) Normal / Burst (Approx.0.85 fps at 12.1MP (Maximum 100 shots))  Built-In ISO Auto: Approx.0.5 - Approx.3.0m (Approx.1.64"-Approx.9.84")(W) / Approx.0.5 - Approx.1.5 m(Approx.1.64"-Approx.4.92")(T), ISO3200: up to Approx.6.0 m(Approx.19.69")(W)
Intelligent Auto Focus Macro Mode  xposure  Exposure Metering Exposure Compensation ISO Backlight Correction HDR Dynamic Range Optimizer  White Balance  hutter Shutter Speed Burst Mode  lash Flash Type	iAUTO(W:Approx. 5cm (1.96°) to Infinity, T:Approx. 50cm (19.7°) to Infinity)  Multi Pattern / Center Weighted / Spot Plus / Minus 2.0EV, 1 / 3EV step Auto / 100 / 200 / 400 / 800 / 1600 / 3200  - Auto / Daylight / Cloudy / Fluorescent 1 (White Fluorescent Lighting) / Fluorescent 2 (Natural White Fluorescent Lighting) / Fluorescent 3 (Day White Fluorescent Lighting) / Incandescent /Flash  iAUTO(1/4" - 1/2.000) / Program Auto(1" - 1/2.000) Normal / Burst (Approx.0.85 fps at 12.1MP (Maximum 100 shots))  Built-In ISO Auto: Approx.0.5 - Approx.3.0m (Approx.1.64'-Approx.9.84')(W) / Approx.0.5 - Approx.1.5 m(Approx.1.64'-Approx.4.92')(T),

eatures Scene Modes	High Sensitivity / Twilight / Twilight Portrait / Soft Snap / Landscape / Beach / Snow / Gourmet
Image Stabilization GPS	SteadyShot®image stabilization
Panorama	_
Multi-shot layering	-
Intelligent Auto	Yes
Intelligent Scene Recognition	7 scenes
Face Detection	8 faces (Auto / Off )
Motion Detection	-
Blink Detection	-
Smile Shutter™ Technology	Yes
Self-timer	Off / 10sec. / 2sec.
In-Camera Editing	Trimming / Red Eye Correction
TransferJet™ Technology	-
puts & Outputs	
USB	Yes - USB2.0 Hi-Speed
HD Video	-
SD Video	Yes
ower	
Supplied Battery	Lithium-ion NP-BN1 3.6V
Battery Life (Approx.)	110
Number of Images (Approx.)	220
eights & Measurements	3 7/8″x2 1/4″x 3/4″
Dimensions (Approx.)	(95.3mmx55mmx18.7mm)
	Approx. 4.3 oz. (121g) body only; Approx. 4.8 oz. (137g)
Weights (Approx.)	With battery and Memory Stick PRO Duo media.
oftware	Will ballery and Memory Slick FRO Dao Media.
	Picture Motion Browser Ver 5.0, PMB Portable 5.0
Supplied Software	(for Windows) <sup>2</sup> , PMB Portable 1.1(for Macintosh)
	PMB and PMB Portable: Microsoft Windows XP SP3,
Operating System	Windows Vista SP2, Windows 7. PMB Portable also
Requirements	compatible with Macintosh OS X(v10.4 - 10.6).
ervice & Warranty	
Limited Term Warranty	Limited 1 Year Parts & Labor
upplied Accessories	
upplied Accessories Battery	BC-C\$N
Battery	
Battery Battery Charger	BC-CSN Yes Yes
Battery Battery Charger A/V Cable	Yes
Battery Battery Charger	Yes
Battery Battery Charger A/V Cable USB Cable Multi-Connector Cable	Yes
Battery Battery Charger A/V Cable USB Cable	Yes
Battery Battery Charger A/V Cable USB Cable Multi-Connector Cable (A/V / USB)	Yes Yes -
Battery Battery Charger A/V Cable USB Cable Multi-Connector Cable (A/V / USB) Shoulder Strap	Yes Yes -
Battery Battery Charger A/V Cable USB Cable Multi-Connector Cable (A/V / USB) Shoulder Strap Wrist Strap	Yes Yes -
Battery Battery Charger A/V Cable USB Cable Multi-Connector Cable (A/V / USB) Shoulder Strap Wrist Strap Lens Cap Tether	Yes Yes Yes

- Footnotes

  1. Viewable area measured diagonally

  2. PMB requires Microsoff® Windows® XP SP3/ Windows Vista® SP2/Windows 7. Picture Motion Browser software not supported by Mac OS. Movie format is compatible with iMovie® '09 or later versions.

  3. PMB Portable is pre-loaded. PMB Portable requires USB cable (included) and PC with internet connectivity. Windows® XP SP3 64-bit and Starter Edition and Windows Vista® Starter Edition
- environments not supported.

  13. When using movie mode Memory Stick PRO Duo<sup>™</sup> with MARK2 (M2) logo, Memory Stick PRO-HG<sup>™</sup>, or SD/SDHC (Class 4 or higher) media are recommended.

L









2.7" LCD1

PINK